2-HYDROXY ETHYL ACRYLATE
Technical Data Sheet（TDS）

Product Name	2-HYDROXY ETHYL ACRYLATE		
Product Alias	2-HYDROXYETHYL PROP-2-ENOATE		
Application	Mainly used in heat curing acrylic coatings, light curing acrylic coatings, photographic coatings, water-soluble electroplating coatings, adhesives, textile treatments, and modifiers for ester processing prepolymers.		
CAS No.	818-61-1	HS CODE	29161290.90
EC No.		212-454-9	
Molecular Weight	116.12	Molecular Formula	$C_5H_8O_3$
Monoester（W.%）	≥93%	Purity（W.%）	≥97%
Water（W.%）	≤ 0.2	Acid（W.%）	≤ 0.2
Inhibitor（MEHQ，CAS#：150-76-5）	180-440ppm	Color（Hazen）	≤ 2 5
Appearance	Colorless clear transparent liquid, no mechanical impurities.		
Density（g/m³）	1.109	Vapor Density（g/m³）	1
Octanol Water partition coefficient	-0.21	Refraction index（20℃）	1.448
Boiling Point	82℃(6.66kPa)	Melting point（℃）	-70
Flash Point（℃）	104（open） 99（Close）	Spontaneous combustion temperature（℃）	≥300
Vapor pressure（kPa）	0.0523 mmHg	Decomposition temperature（℃）	≥300
Evaporation rate（kg/S）	≤0.01	Viscosity mPa.s（20℃）	5.34
Specific heat cal/g℃	0.5	Polymerization heat kcal/mol	/
Solubility % (underwater)	/	Solubility % (water in material)	/
Explosive range air VOL%	2.5—	Toxicity (rodent)LD50mg/kg	1070
Solubility	Soluble in organic solvents.		
Prohibition on disposable material	Strong redox agents, acids, peroxides, heavy metal salts.		
Packing	Polyethylene plastic drums, IBC, Teflon lined iron drums, ISO TANK tanks.		

DECHEM GROUP LTD

Address：No.9 Xinyuan Road, Tancheng County Economic Development Zone, Linyi City, Shandong Province, China
Zip code: 276100
TEL：+8615165538198
Email：sales.samsun@dechemgroup.com